



Bearing No.	Boundary dimensions				Basic load ratings (kN)		Limiting speed		Mass
	mm				Dynamic	Static	rpm		Kg
	d	D	B	rs min	Cr	Cor	Grease	Oil	
6300	10	35	11	0.6	7.65	3.48	23000	27000	0.053
6301	12	37	12	1	9.72	5.08	20000	24000	0.061
6302	15	42	13	1	11.5	5.42	17000	21000	0.08
6303	17	47	14	1	13.5	6.58	16000	19000	0.109
6304	20	52	15	1.1	15.8	7.88	14000	17000	0.142
6305	25	62	17	1.1	22.2	11.5	12000	14000	0.219
6306	30	72	19	1.1	27	15.2	10000	12000	0.349
6307	35	80	21	1.5	33.2	19.2	8800	10000	0.455
6308	40	90	23	1.5	40.8	24	7800	9200	0.639
6309	45	100	25	1.5	52.8	31.8	7000	8200	0.873
6310	50	110	27	2	62	38.3	6400	7500	1.07
6311	55	120	29	2	71.6	45	5800	6800	1.37
6312	60	130	31	2.1	81.9	52.2	5400	6300	1.7
6313	65	140	33	2.1	92.7	59.9	4900	5800	2.08
6314	70	150	35	2.1	104	68.2	4600	5400	2.52
6315	75	160	37	2.1	113	77.2	4300	5000	3.02
6316	80	170	39	2.1	123	86.7	4000	4700	3.59

<b>6317</b>	85	180	41	3	133	96.8	3800	4500	4.23
<b>6318</b>	90	190	43	3	143	107	3600	4200	4.91
<b>6319</b>	95	200	45	3	153	119	3300	3900	5.67
<b>6320</b>	100	215	47	3	173	141	3200	3700	7
<b>6321</b>	105	225	49	3	184	153	3000	3600	8.05
<b>6322</b>	110	240	50	3	205	180	2900	3400	9.54
<b>6324</b>	120	260	55	3	207	185	2600	3100	12.4
<b>6326</b>	130	280	58	4	229	214	2400	2800	15.3
<b>6328</b>	140	300	62	4	253	246	2200	2600	18.5
<b>6330</b>	150	320	65	4	274	284	2100	2400	22
<b>6332</b>	160	340	68	4	278	286	1900	2300	26
<b>6334</b>	170	360	72	4	325	355	1800	2100	30.7
<b>6336</b>	180	380	75	4	355	405	1700	2000	35.6
<b>6338</b>	190	400	78	5	355	415	1600	1900	41
<b>6340</b>	200	420	80	5	410	500	1500	1800	46.3
<b>6344</b>	220	460	88	5	410	520	1400	1600	60.8