



Bearing No.	Boundary dimensions				Basic load ratings (kN)		Limiting speed		Mass
	mm				Dynamic	Static	rpm		Kg
	d	D	B	rs min	Cr	Cor	Grease	Oil	
16001	12	28	7	0.3	5.1	2.39	26000	30000	0.019
16002	15	32	8	0.3	5.6	2.83	22000	26000	0.025
16003	17	35	8	0.3	6.8	3.35	20000	24000	0.032
16004	20	42	8	0.3	7.9	4.5	18000	21000	0.051
16005	25	47	8	0.3	8.35	5.1	15000	18000	0.06
16006	30	55	9	0.3	11.2	7.35	13000	15000	0.091
16007	35	62	9	0.3	11.7	8.2	12000	14000	0.11
16008	40	68	9	0.3	12.6	9.65	10000	12000	0.125
16009	45	75	10	0.6	12.9	10.5	9200	11000	0.171
16010	50	80	10	0.6	13.2	11.3	8400	9800	0.18
16011	55	90	11	0.6	18.6	15.3	7700	9000	0.258
16012	60	95	11	0.6	20	17.5	7000	8300	0.283
16013	65	100	11	0.6	20.5	18.7	6500	7700	0.307
16014	70	110	13	0.6	24.4	22.6	6100	7100	0.441
16015	75	115	13	0.6	25	24	5700	6700	0.464
16016	80	125	14	0.6	25.4	25.1	5300	6200	0.597
16017	85	130	14	0.6	25.9	26.2	5000	5900	0.626
16018	90	140	16	1	33.5	33.5	4700	5600	0.848
16019	95	145	16	1	34.5	35	4500	5300	0.885

<b>16020</b>	100	150	16	1	35	36.5	4200	5000	0.91
<b>16021</b>	105	160	18	1	52	50.5	4000	4700	1.2
<b>16022</b>	110	170	19	1	57.5	56.5	3800	4500	1.46
<b>16024</b>	120	180	19	1	63	63.5	3500	4100	1.56
<b>16026</b>	130	200	22	1.1	80	79.5	3200	3800	2.31
<b>16028</b>	140	210	22	1.1	82	85	3000	3500	2.45
<b>16030</b>	150	225	24	1.1	96.5	101	2800	3200	3.07
<b>16032</b>	160	240	25	1.5	99	108	2600	3000	3.64
<b>16034</b>	170	260	28	1.5	119	128	2400	2800	4.93
<b>16036</b>	180	280	31	2	117	134	2300	2700	6.49
<b>16038</b>	190	290	31	2	134	156	2100	2500	6.77
<b>16040</b>	200	310	34	2	142	160	2000	2400	8.68